Reset the MySQL/MariaDB Root Password

By default, the MySQL/MariaDB installation that ships with XAMPP has an empty root password. This is a serious security risk, especially if you plan to use XAMPP in production scenarios.

To change the MySQL/MariaDB root password, follow these steps:


1. Ensure that the MySQL/MariaDB server is running.
2. Open a new Linux terminal.
3. Use the *mysqladmin* command-line utility to alter the MySQL/MariaDB password, using the following syntax:

   ```
   mysqladmin --user=root password "newpassword"
   ```

   The *mysqladmin* command-line utility is located within the *bin/* subdirectory of the XAMPP installation directory, typically */opt/lampp*.

   For example, to change the MySQL/MariaDB root password from its default empty value to the password *gue55me*, you would execute:

   ```
   /opt/lampp/bin/mysqladmin --user=root password "gue55me"
   ```

   Or, if a password has already been previously set and you'd like to change it to a new one, you can use the following syntax:

   ```
   mysqladmin --user=root --password=oldpassword password "newpassword"
   ```

   For example, to change the root password from *12345* to *gue55me*, you would execute:

   ```
   /opt/lampp/bin/mysqladmin --user=root --password=12345 password "gue55me"
   ```

4. Test that your password change has been accepted, by attempting to connect to the MySQL/MariaDB server using the *mysql* command-line client in the same directory. For example, you could use the command below to connect to the server and return the results of a calculation:

```
/opt/lampp/bin/mysql --user=root --password=gue55me -e "SELECT 1+1"
```

